

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 8-10-2018 Revision date: 28-7-2021 Supersedes version of: 13-7-2020 Version: 4.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Carb Cleaner
JY-300U-NVTC
,
t
oduct
). 7

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category Use of the substance/mixture : Industrial use,Professional use,Consumer use: Degreasing product

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Putoline Oil Dollegoorweg 15 7602 EC Almelo - Netherlands T 0031 (0)546 81 81 65 vib@putoline.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412
Full text of H-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC)	No. 1272/2008 [CLP]
Hazard pictograms (CLP)	GHS02 GHS07
Signal word (CLP)	: Danger
Contains	 ethyl acetate; Hydrocarbons, C9, aromatics; Hydrocarb cyclics, <2% aromatics
Hazard statements (CLP)	: H222 - Extremely flammable aerosol.
	H229 - Pressurised container: May burst if heated.
	H319 - Causes serious eye irritation.
	H336 - May cause drowsiness or dizziness.
	H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product conta

 Precautionary statements (CLP)
 : P101 - If medical advice is needed, have product container or label at hand.

 P102 - Keep out of reach of children.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

 No smoking.
 P211 - Do not spray on an open flame or other ignition source.

 P251 - Do not pierce or burn, even after use.
 P271 - Use only outdoors or in a well-ventilated area.

 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

 EUH-statements
 : EUH066 - Repeated exposure may cause skin dryness or cracking.

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethyl acetate substance with national workplace exposure limit(s) (GB, IE); substance with a Community workplace exposure limit	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Butane substance with national workplace exposure limit(s) (GB, IE) (Note K)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Propane substance with a Community workplace exposure limit (Note U)	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Hydrocarbons, C9-C11, n-alkanes, isoalkanes,

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C9, aromatics	(CAS-No.) 128601-23-0 (EC-No.) 918-668-5 (REACH-no) 01-2119455851-35	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	(CAS-No.) 64742-48-9 (EC-No.) 919-857-5 (REACH-no) 01-2119463258-33	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
isobutane substance with national workplace exposure limit(s) (IE) (Note K)	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (REACH-no) 01-2119485395-27	2,5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Note K: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures 4.1. Description of first aid measures First-aid measures general ÷ Call a physician immediately. First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. First-aid measures after skin contact Wash skin with plenty of water. First-aid measures after eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. 4.2. Most important symptoms and effects, both acute and delayed Symptoms/effects : May cause drowsiness or dizziness. Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking. Symptoms/effects after eye contact : Eye irritation. Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measu	res	
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide. : Do not use a heavy water stream.	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard	 Extremely flammable aerosol. Pressurised container: May burst if heated. 	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release m	easures
6.1. Personal precautions, protective	equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for contain	ment and cleaning up
Methods for cleaning up Other information	Mechanically recover the product.Dispose of materials or solid residues at an authorized site.
6.4 Reference to other sections	

For further information refer to section 13.

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.	
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.	

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection		
8.1. Control parameters		
8.1.1 National occupational exposure and biological limit values		
ethyl acetate (141-78-6)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Ethyl acetate	

734 mg/m³

IOEL TWA

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethyl acetate (141-78-6)		
IOEL STEL	1486 mg/m ³	
IOEL STEL [ppm]	400 ppm	
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164	
Ireland - Occupational Exposure Limits		
Local name	Ethyl acetate	
OEL TWA [1]	734 mg/m³	
OEL TWA [2]	200 ppm	
OEL STEL	1468 mg/m ³	
OEL STEL [ppm]	400 ppm	
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
Local name	Ethyl acetate	
WEL TWA (OEL TWA) [1]	734 mg/m³	
WEL TWA (OEL TWA) [2]	200 ppm	
WEL STEL (OEL STEL)	1468 mg/m ³	
WEL STEL (OEL STEL) [ppm]	400 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Butane (106-97-8)		
Ireland - Occupational Exposure Limits		
Local name	Butane, all isomers: Butane	
OEL STEL [ppm]	1000 ppm	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
Local name	Butane	
WEL TWA (OEL TWA) [1]	1450 mg/m³	
WEL TWA (OEL TWA) [2]	600 ppm	
WEL STEL (OEL STEL)	1810 mg/m³	
WEL STEL (OEL STEL) [ppm]	750 ppm	
Remark (WEL)	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Propane (74-98-6)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA [ppm] 1000 ppm		
Ireland - Occupational Exposure Limits		
Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Propane (74-98-6)	
Notes (IE)	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)
Regulatory reference	Chemical Agents Code of Practice 2020

isobutane (75-28-5)		
Ireland - Occupational Exposure Limits		
Local name	Butane, all isomers: Isobutane	
OEL STEL [ppm]	1000 ppm	
Regulatory reference	Chemical Agents Code of Practice 2020	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:			
Safety glasses			
Туре	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

8.2.2.2. Skin protection

Skin and body protection:	
Wear suitable protective clothing	

Hand protection:					
Protective gloves					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Colour:ColOdour:chaOdour threshold:NopH:NoRelative evaporation rate (butylacetate=1):NoMelting point:NoFreezing point:NoBoiling point:-44Flash point:-97Critical temperature:270Auto-ignition temperature:No	rosol. ourless to Amber. iracteristic. data available data available data available
Odour:chaOdour threshold:NopH:NoRelative evaporation rate (butylacetate=1):NoMelting point:NoFreezing point:NoBoiling point:-44Flash point:-97Critical temperature:270Auto-ignition temperature:No	rracteristic. data available data available data available data available
Odour threshold:NopH:NoRelative evaporation rate (butylacetate=1):NoMelting point:NoFreezing point:NoBoiling point:-44Flash point:-97Critical temperature:270Auto-ignition temperature:No	data available data available data available
pH:NoRelative evaporation rate (butylacetate=1):NoMelting point:NoFreezing point:NoBoiling point:-44Flash point:-97Critical temperature:270Auto-ignition temperature:No	data available data available
Relative evaporation rate (butylacetate=1): NoMelting point: NoFreezing point: NoBoiling point: -44Flash point: -97Critical temperature: 270Auto-ignition temperature: No	data available
Melting point: NotFreezing point: NoBoiling point: -44Flash point: -97Critical temperature: 270Auto-ignition temperature: No	
Freezing point:NoBoiling point:-44Flash point:-97Critical temperature:270Auto-ignition temperature:No	
Boiling point: -44Flash point: -97Critical temperature: 270Auto-ignition temperature: No	applicable
Flash point: -97Critical temperature: 270Auto-ignition temperature: No	data available
Critical temperature : 270 Auto-ignition temperature : No	°C
Auto-ignition temperature : No	°C
	2° (
Decomposition temperature : No	data available
	data available
Flammability (solid, gas) : Ext	remely flammable aerosol.
Vapour pressure : 360	00 hPa
Relative vapour density at 20 °C : No	data available
Relative density : No	data available
Density : 0,6	99 g/cm³ at 20 °C
Solubility : Wa	ter: Insoluble / Slightly miscible
Partition coefficient n-octanol/water (Log Pow) : No	data available
Viscosity, kinematic : < 2	0,5 mm²/s (40 °C) - ASTM D7279
Viscosity, dynamic : No	data available
Explosive properties : Pre	ssurised container: May burst if heated.
Oxidising properties : No	
Lower explosive limit (LEL) : 0,6	data available
Upper explosive limit (UEL) : 11,	data available vol %

9.2. Other information

VOC content

: 699,9 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological in	nformation	
11.1 Information on toxicologica	l effects	
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	Not classifiedNot classifiedNot classified	
ethyl acetate (141-78-6)		

LD50 oral	5620 mg/kg bodyweight
LD50 dermal	> 18000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	57700 mg/l

Hydrocarbons, C9, aromatics (128601-23-0)	
LD50 oral rat	3492 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 3160 mg/kg (OECD 402 method)
LC50 Inhalation - Rat	> 6193 mg/m³ (OECD 403 method)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 5000 mg/kg (OECD 402 method)
LC50 Inhalation - Rat	> 5000 mg/m³ (OECD 403 method)

: Not classified
: Causes serious eye irritation.
: Not classified
: May cause drowsiness or dizziness.
May cause drowsiness or dizziness.

Hydrocarbons, C9, aromatics (128601-23-0)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)			
STOT-single exposure	May cause drowsiness or dizziness.		
STOT-repeated exposure :	Not classified		
Aspiration hazard :	May be fatal if swallowed and enters airways.		
Putoline Carb Cleaner			
Vaporizer	aerosol		
Viscosity, kinematic	< 20,5 mm²/s (40 °C) - ASTM D7279		

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term	: Not classified
(acute) Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

ethyl acetate (141-78-6)		
LC50 - Fish [1]	230 mg/l	
EC50 - Other aquatic organisms [1]	717 mg/l waterflea	
EC50 - Other aquatic organisms [2]	3300 mg/l	

Hydrocarbons, C9, aromatics (1	8601-23-0)
LC50 - Fish [1]	9,2 mg/l (96h, Oncorhynchus mykiss)
EC50 - Crustacea [1]	3,2 mg/l (48h, Daphnia magna)
ErC50 algae	2,9 mg/l (72h, Pseudokirchneriella subcapitata)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)			
LC50 - Fish [1]	> 1000 mg/l (Oncorhynchus mykiss, 96h) [OCDE 203]		
EC50 - Crustacea [1]	> 1000 mg/l (Daphnia magna, 48h) [OCDE 202]		
ErC50 algae	> 1000 mg/l (Pseudokirchnerella subcapitata, 72h) [OCDE 201]		

12.2. Persistence and degradability

Hydrocarbons, C9, aromatics (128601-23-0)		
Persistence and degradability Readily biodegradable.		
Biodegradation	78 % (28d)	

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)			
Persistence and degradability Readily biodegradable, according to appropriate OECD test.			
12.3. Bioaccumulative potential			
ethyl acetate (141-78-6)			
Partition coefficient n-octanol/water (Log Pow)	0,7		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C9, aromatics (128601-23-0)			
Bioconcentration factor (BCF REACH)	≥ 500		
Partition coefficient n-octanol/water (Log Kow)	≥ 4 Octanol/water coefficient		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes	, cyclics, <2% aromatics (64742-48-9)		
Bioconcentration factor (BCF REACH)	≥ 500		
Partition coefficient n-octanol/water (Log Kow)	≥ 4 Octanol/water coefficient		
12.4. Mobility in soil			
Hydrocarbons, C9, aromatics (128601-23-0)			
Ecology - soil	Extremely volatile.		
12.5. Results of PBT and vPvB assessment			
Component			
Hydrocarbons, C9, aromatics (128601-23-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
12.6. Other adverse effects			

No additional information available

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste treatment methods European List of Waste (LoW) code HP Code	 Dispose of contents/container in accordance with licensed collector's sorting instructions. 20 01 13* - solvents 15 01 04 - metallic packaging HP3 - "Flammable:" flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and < 75 °C; flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP4 - "Irritant — skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG		ΙΑΤΑ	ADN	RID
14.1. UN number					
UN 1950	UN 1950		UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	a nomo				
	-		Asussels flammable		
AEROSOLS	AEROSOLS		Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption				
UN 1950 AEROSOLS, 2.1, (D)	, UN 1950 AEROSOLS, 2.1		UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard o	lass(es)				
2.1	2.1		2.1	2.1	2.1
2	~		2		
14.4. Packing group					-
Not applicable	Not applicable		Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No		Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary informatio	n available				
14.6. Special precaution	s for user				
Overland transport Classification code (ADR) Special provisions (ADR) Limited quantities (ADR) Excepted quantities (ADR) Packing instructions (ADR) Special packing provisions (A Mixed packing provisions (AD Transport category (ADR) Special provisions for carriage Special provisions for carriage and handling (ADR) Special provisions for carriage and handling (ADR)	R) : e - Packages (ADR) : e - Loading, unloading : e - Operation (ADR) :	1I E0 P20 PP MP 2 V14	87, RR6, L2 9		
Transport by sea Special provisions (IMDG) Packing instructions (IMDG) Special packing provisions (IM EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG) Stowage and handling (IMDG Segregation (IMDG) Air transport	/DG)	63, P2(PP F-E S-L	J ne /1, SW22		

Air transport	
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provisions (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L
Inland waterway transport		
Classification code (ADN)	:	5F
Special provisions (ADN)	:	190, 327, 344, 625
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E0
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01, VE04
Number of blue cones/lights (ADN)	:	1
Rail transport		
Classification code (RID)	:	5F
Special provisions (RID)	:	190, 327, 344, 625
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E0
Packing instructions (RID)	:	P207, LP200
Special packing provisions (RID)	:	PP87, RR6, L2
Mixed packing provisions (RID)	:	MP9
Transport category (RID)	:	2
Special provisions for carriage – Packages (RID)	:	W14
Special provisions for carriage - Loading, unloading	:	CW9, CW12
and handling (RID)		
Colis express (express parcels) (RID)	:	CE2
Hazard identification number (RID)	:	23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content	:	699,9 g/l
Child-resistant fastening	:	Not applicable
Tactile warning	:	Not applicable

Detergent Regulation : Labelling of contents (648/2004/EC):		
Component	%	
aliphatic hydrocarbons	≥30%	
aromatic hydrocarbons	5-15%	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
9.1	Colour	Added	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
vPvB	Very Persistent and Very Bioaccumulative	
WGK	Water Hazard Class	

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Comp.)	Gases under pressure : Compressed gas
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.